Full Colour Multi Function Printer

RICOH IM C3000 IM C4500 IM C6000





Welcome to a new era of technology that keeps your workplace up to date with RICOH IM C3000 / C4500 / C6000 range of intelligent devices. Device and technology that is designed to grow and adapt, just as your business does.

Today's workplace needs to be ready for tomorrow. RICOH Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, usingtechnology that is scalable, secure, sustainable and simple.

Now is the time to:

- Protect your devices with easy access to security updates
- Take advantage of easy productivity upgrades at your own pace
- Save costs by bringing high-standard quality print output in-house
- Maximise productivity with streamlined workflows





Excellent Performance with the Best Quality Output

Greater Control of Scan and Print Management

Scanning of smaller sized documents can be easily done with the new small sized paper scan unit. The double feed detection unit helps to improve scan accuracy while the EFI controller enhances print management. Now, you can also create professional grade flyers at your own convenience with our inner multi-folding unit.



Seamless User Experience

Our intelligent devices offer efficient working and reduced user intervention by expanding paper capacity. Choose from our versatile finishing and paper options for a professional touch to save time and reduce outsourcing expenses. With RICOH Intelligent Support, experience maximum device uptime and minimal disruption across all your devices.





Maximise Cost Savings

Enjoy lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of RICOH Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device – avoiding the need for intervention by more costly IT resources.



Next-level Productivity with Smart Operations

Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device with built in support for NFC, AirPrint or Mopria. All this underpinned by a unique suite of support apps from RICOH Smart Integration.

RICOH IM C3000 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM	C4500	RICOH IM C6000	
GENERAL					
Warm-up Time		21 Seco	nds		
First Output Speed : B/W	4.5 Seconds	3.6 Seco	onds	2.9 Seconds	
First Output Speed : Full Color	6.9 Seconds	5.4 Seco	onds	4.2 Seconds	
Continuous Output Speed	30ppm			60ppm	
Memory Std/Max		2GB Std / 4GB Max			
HDD Std/Max	320GB Std/ 4GB Max				
ARDF Capacity	100 Sheets				
SPDF Capacity	220 Sheets				
Weight [Mainframe]				Less Than 87 5Kg	
Dimensions W x D x H [Standard]	Less Than 85.5Kg Less Than 87.5Kg 587 x 685 x 788 mm				
Dimensions W x D x H [Maximum]					
(excluding ARDF/SPDF)		668 x 738 x 1	1030 mm		
Power Source		220 - 240V 5	50/60Hz		
COPIER					
Multiple Copying		Up to 999	Copies		
Resolution		600 dp	pi		
Zoom		From 25% to 400°	% in 1% Step		
PRINTER					
CPU	Intel Atom Processor ApolloLal	ke 1.3GHz	Intel Ato	m Processor ApolloLake 1.6GHz	
Printer Language : Standard	PCL5c,	PCL6, Postscript 3 (emulat		· · · · · · · · · · · · · · · · · · ·	
Printer Language : Option	Genuine Adobe	® Postscript®3™, XPS, IPDS	5, PictBridge, PDF Dire	ect from Adobe®	
Print Resolution		1,200 x 1,2			
Network Interface : Standard	Ethernet 10 base-T/	100base-TX/1000 base-T, U	•	JSB Device I/F Type B	
Network Interface : Option		84/ECP, Wireless LAN (IEEE			
Mobile Printing Capability		Mopria, Google Cloud Pri			
- ' -				er 2008R2, Windows® Server 2012R2,	
Windows® environments		Windows® Sei			
	Macintosh OS X10.11 or Later				
Mac OS environments		Macintosh OS X1	0.11 or Later		
	UNIX Sun® Solar	Macintosh OS X1 is, HP-UX, SCO OpenServe		erprise, IBM® AIX	
Mac OS environments	UNIX Sun® Solar		r, RedHat® Linux Ente	erprise, IBM® AIX	
Mac OS environments UNIX environments	UNIX Sun® Solar	is, HP-UX, SCO OpenServe	r, RedHat® Linux Ente /4®	erprise, IBM® AIX	
Mac OS environments UNIX environments SAP® environments	UNIX Sun® Solar	is, HP-UX, SCO OpenServe SAP® S/	r, RedHat® Linux Ente /4®	erprise, IBM® AIX	
Mac OS environments UNIX environments SAP® environments Other Supported environments	UNIX Sun® Solar	is, HP-UX, SCO OpenServe SAP® S/	rr, RedHat® Linux Ente /4® ries	erprise, IBM® AIX	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER	UNIX Sun® Solar	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer	r, RedHat® Linux Ente /4® ries 240ipm (duplex)	erprise, IBM® AIX	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed	UNIX Sun® Solar	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2	er, RedHat® Linux Ento /4® ries 240ipm (duplex) dpi	erprise, IBM® AIX	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 d TIFF (MH, MR, MMR,	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSen 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High co	rr, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi I	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSel 120ipm (Simplex) / 2 1,200 d TIFF (MH, MR, MMR, MPF, MPF, Single Page High con	rr, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi I	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSel 120ipm (Simplex) / 2 1,200 d TIFF (MH, MR, MMR, MPF, MPF, Single Page High con	rr, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi I SB, SD Card	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 d TIFF (MH, MR, MMR, JPEG, Single Page High con PDF, Multi page High con	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi I SB, SD Card	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con PDF, Multi page High con Email, Folder, U:	rr, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi SB, SD Card	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secon	rr, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi I SB, SD Card PBX nds pps 200 x 100 dpi	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi I SB, SD Card BBX nds pps 200 x 100 dpi 400 x 400 dpi	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 of TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, Ut PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm,	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi SB, SD Card BBX nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, MH, MR, MM	er, RedHat® Linux Ente //4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi I SB, SD Card PBX ands apps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secon 33.6 Kb 8 x 3.65 line/mm, MH, MR, MM 4MB (320 f	er, RedHat® Linux Ente //4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi I SB, SD Card PBX ands apps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum	Single Page TIFF, Single page .	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secon 33.6 Kb 8 x 3.65 line/mm, MH, MR, MM 4MB (320 f	er, RedHat® Linux Enter 4/4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single npression PDF, Multi I SB, SD Card BBX nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages)	e page PDF-A, Multi page TIFF,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING	Single Page TIFF, Single page Multi page	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 of TIFF (MH, MR, MMR, JPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MM 4MB (320 f) 60MB (4,800	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi I SB, SD Card PBX nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages)	e page PDF-A, Multi page TIFF, Page PDF-A	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size	Single Page TIFF, Single page Multi page	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MM 4MB (320 F 60MB (4,800	er, RedHat® Linux Enter 4/4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX nds 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa	e page PDF-A, Multi page TIFF, Page PDF-A	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std	Single Page TIFF, Single page Multi page	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MM 4MB (320 F 60MB (4,800) SRA3, A3, A4, A5,	er, RedHat® Linux Enter 4/4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card BBX nds 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets	e page PDF-A, Multi page TIFF, Page PDF-A	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max	Single Page TIFF, Single page Multi page	is, HP-UX, SCO OpenServe SAP® S/ IBM iSei 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, IPEG, Single Page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MM 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, 100 Sheets (550 Sheet x 2 tr	er, RedHat® Linux Enter 4/4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card BBX nds 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets	e page PDF-A, Multi page TIFF, Page PDF-A	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max	Single Page TIFF, Single page Multi page	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, JPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, 100 Sheets (550 Sheet x 2 tr 4,700 Sheets (550 Sheet x 2 tr	er, RedHat® Linux Ente (40° ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ands 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets	e page PDF-A, Multi page TIFF, Page PDF-A	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std	Single Page TIFF, Single page Multi page Multi page 1,20 1,625 Sheets	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, MR, MR, MR, MR, MR, MR, MR, M	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ads 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets g/m² etterhead, Cardstock,	e page PDF-A, Multi page TIFF, Page PDF-A sss) 3,625 Sheets Preprinted paper, Bond paper,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight	Single Page TIFF, Single page Multi page Multi page 1,20 1,625 Sheets	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, IPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, x 00 Sheets (550 Sheet x 2 tr 4,700 She 500 Sheet x 2 tr 60 - 300c ecial paper, Color paper, Lee	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ads 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets g/m² etterhead, Cardstock,	e page PDF-A, Multi page TIFF, Page PDF-A sss) 3,625 Sheets Preprinted paper, Bond paper,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Max Paper Output Capacity Max Paper Weight Paper Types	Single Page TIFF, Single page Multi page Multi page 1,20 1,625 Sheets	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, IPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, x 00 Sheets (550 Sheet x 2 tr 4,700 She 500 Sheet x 2 tr 60 - 300c ecial paper, Color paper, Lee	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ads 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets g/m² etterhead, Cardstock,	e page PDF-A, Multi page TIFF, Page PDF-A sss) 3,625 Sheets Preprinted paper, Bond paper,	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution : Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Std Paper Weight Paper Types ECOLOGY	Single Page TIFF, Single page Multi page Multi page 1,20 1,625 Sheets Plain paper, Recycle paper, Spe	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, IPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, x 00 Sheets (550 Sheet x 2 tr 4,700 She 500 Sheet x 2 tr 60 - 300c ecial paper, Color paper, Lee	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ads 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets g/m² etterhead, Cardstock,	e page PDF-A, Multi page TIFF, Page PDF-A sss) 3,625 Sheets Preprinted paper, Bond paper, OHP	
Mac OS environments UNIX environments SAP® environments Other Supported environments SCANNER Scanning Speed Resolution: Maximum Compression Method File Formats Scan Modes FACSIMILE Circuit Tranmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY Power Consumption: Max	Single Page TIFF, Single page Multi page Multi page 1,20 1,625 Sheets Plain paper, Recycle paper, Spe Coa	is, HP-UX, SCO OpenServe SAP® S/ IBM iSer 120ipm (Simplex) / 2 1,200 c TIFF (MH, MR, MMR, IPEG, Single Page High con PDF, Multi page High con Email, Folder, U: PSTN, P 2 Secor 33.6 Kb 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 F 60MB (4,800 SRA3, A3, A4, A5, x 00 Sheets (550 Sheet x 2 tr 4,700 She 500 Sheet x 2 tr 60 - 300c ecial paper, Color paper, Lee	er, RedHat® Linux Ente /4® ries 240ipm (duplex) dpi JBIG2), Grayscale mpression PDF, Single mpression PDF, Multi SB, SD Card PBX ads 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) D Pages) A6, B4, B5, B6 rays + 100 Sheet bypa eets eets g/m² etterhead, Cardstock,	e page PDF-A, Multi page TIFF, Page PDF-A sss) 3,625 Sheets Preprinted paper, Bond paper, OHP Less Than 1,850 W	

RICOH IM C3000 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C4500	RICOH IM C6000		
OUTPUT TRAY AND FINISHER OPTION					
1 x 550-Sheets Paper Tray (PB 3270)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²				
2 x 550-Sheets Paper Tray (PB 3280)		Paper Size : A6-SRA3, Paper Weight : 60-300g/m²			
2,000-Sheets Large Capacity Tray (LCIT PB3290)		Paper Size : A4, Paper Weight : 60-300g/m²			
1,500-Sheets Large Capacity Tray (LCIT RT3040)		Paper Size : A4, Paper Weight : 60-300g/m²			
1,000-Sheets Hybrid Finisher (SR3260)	Staple paper size : A4-A	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3) Stapleless capacity Max : 5 sheets (A4/A3)			
3,000-sheet Finisher (SR 3280) [Available for IM C4500, IM C6000 only]	Staple paper size : A4-A3, Sta	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Top slant Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)			
1,000-Sheet Booklet Finisher (SR3270)	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)				
2,000-Sheet Booklet Finisher (SR3290) [Available for IM C4500, IM C6000 only]	Staple paper size : A4-A3, Št	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Booklet tray: A4-A3 Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples, Booklet Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)			
500-Sheet Internal Finisher (SR3250) (IM C6000 is not supported)		Paper Size: A6-A3, Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)			
250-Sheet Internal Finisher (SR3300) (Available for IM C3000, IM C3500 only)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top,1 Staple Staple capacity Max : 2-5 sheets (A4)				
Internal Shift Tray (SH3080)	Tray Capacity: 250 sheets, Paper size: 320 mm x 600 mm or smaller, Paper weight: 60-300g/m²				
One-bin tray (BN3130)	Tray Capacity: 125 sheets, Paper size: A5 - A3, Paper weight: 52-300g/m²				

OTHER OPTIONS

Platen Cover PN2000, DF3110, DF3120, Fax Option Type M37, G3 Interface Unit Type M37, Fax Connection unit Type M37, FAX Memory unit Type M19 64MB, Memory Unit Type M37 4GB, Caster Table Type M3, VM Card Type M37, Side Tray, Punch Unit NA/EU/SC (PU3070,PU3080,PU3090), Internal Multi-fold unit FD3010, Camera direct print card, Postscript3 Unit Type M37, XPS direct print Option Type M37, IEEE 1284 I/F Type M19, IEEE 802.11a/g/n I/F Type M19, Device server option Type M37, File format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, ADF Handle, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built in Unit Type M37, External USB Keyboard (No bracket), Color Controller E-25C, Unicode Font Package for SAP®License.

- * For availability of models, optional apparatus and software, please consult your local Ricoh representative.
- * For complete capability of Mac, Unix, Sap and IBM iSeries. Genuine Adobe® Postscript®3™ is required.



URL: http://www.ricoh.co.in

RICOH INDIA LIMITED

CORPORATE OFFICE: 7th, 11th Floors, Tower 'B', Windsor IT Park, A-1, Sector 125, Expressway, Gautam Budh Nagar, Noida, Uttar Pradesh - 201301

Tel: (0120) 4582900, Service toll free number: 1800 103 0066 & 1800 116 600, Email: ril.info@ricoh.co.in REGISTERED OFFICE: Unit No. 1132, 3rd Floor, Building No. 11, Solitaire Corporate Park,

Andheri Ghatkopar Link Road, Chakala, Andheri East, Mumbai - 400 093

Tel: +91 22 66833000 (5 Lines) Fax: +91 22 67032099.

Bangalore, Chennai, Noida, Gurgaon, Hyderabad, Kolkata, Mumbai, Pune.

For more information, please contact:



S2 Cyrils Tower, Railway Station Road, Kottayam-1

Call Now: 0481 2569980, 9446898105